

	The sniffer uses the LCM1602 two line display with nibbles strobed in via an I2C bus. Bit banging proved too slow because the display could not be ready for the next decode so hi2c instructions were used. In turn this meant that the SPI instructions to the radio module had to be done the hard way. Most of the rest of the code involves setting up special characters to give a mimic diagram of the track turnouts and showing the position and status of each tram. The blinking cursor is used if a command is waiting a reply. It would appear that some wireless keyboards use this chip and the key strokes can be hacked using this method.			
	<ul> <li>Attached Thumbnails</li> <li>The second state of the second state of</li></ul>	)		
Blog this Post	·		Reply Reply With Quote	
+ Reply to Thread		Quick Navigation	User Projects - Communication Top	
	« Previous Threa	d   Next Thread »		
Tags for this Thread				
None View Tag Cloud			Add / Edit Tags	
Bookmarks		Posting Permissions		
Digg del.icio.us		You may post new threads You may post replies	<b>BB code</b> is On <b>Smilies</b> are On	

You may post attachments

You may edit your posts

G Ctumblellnen

[IMG] code is On [VIDEO] code is On

28/10/2016	2.46HZ Kadio Shiffer	
<ul> <li>✓ Stumpleupon</li> <li>Google</li> </ul>	Tou may our your posts	HTML code is Off Forum Rules
Picaxe Theme   English (US)		Contact Us Main PICAXE Website Archive Top

All times are GMT +1. The time now is 07:07.

Powered by <u>vBulletin®</u> Version 4.2.2 Copyright © 2016 vBulletin Solutions, Inc. All rights reserved.

(c) Revolution Education Ltd 2007-15